

SERIES A35

TECHNICAL DATA SHEET

Activated Carbon Impregnated Filter Media

1. Product Description

This media is engineered for adsorption of chlorine, taste- and odor-causing compounds, and organic contaminants in water filtration and treatment applications. The activated carbon is bonded directly to a polyester fibers substrate (3.0 oz./sq.yd. uncoated), producing a flexible media that is easy to handle and integrate into water filtration cartridges and OEM treatment systems.

2. Base Fabric / Substrate

Uncoated Weight: 3.0 oz./sq.yd.

Composition: Polyester Fibers

3. Technical Specifications

Style No.	A3552	A3560
Activated Carbon Add-On (%)	108	150
Activated Carbon (grams/sq.yd.)	93.6	127.6
Total Coated Weight (oz./sq.yd.)	6.3	7.5
Nominal Thickness (inches)	0.075"	0.075"

Other activated carbon loadings, thicknesses, and flow rate options available — contact Gremarco to discuss your requirements.

4. Certifications & Regulatory Compliance

- Available with UL 900 certification for flame retardancy, Class 2 (optional)
- Conflict Minerals, TSCA, California Prop 65, REACH, RoHS, and PFAS declarations available at gremarco.com/disclosures
- Safety Data Sheet (A-Series SDS) available at gremarco.com/disclosures

5. Packaging

Standard put-up is 52" wide rolls, approx. 165 linear yards per roll. Rolls can be slit to width or die cut to your exact specifications upon request.

6. Handling & Storage

- Store sealed in a cool, dry environment
- Avoid rough handling to prevent dusting
- Keep away from strong oxidizers (e.g., liquid oxygen)

The information provided is believed to be accurate and representative of the product(s) listed. Gremarco, LLC makes no warranty, either expressed or implied, regarding the suitability of any product(s) listed for any specific use. This Technical Data Sheet does not replace the Safety Data Sheet (SDS); refer to the A-Series SDS at gremarco.com/disclosures for complete handling and safety information.